









# ARE YOU COMPLIANT?

## Masonry

Connection Type to Xtract Vac® Hose	Applicable Models	Attachment Part #
<b>Drilling</b>		
	 Makita® Hammers HRH01, XRH03, XRH04, HR1830F, HR2475, HR2641, HR2811F	193472-7 
3/4" x 10' Hose 192108-A 	 Makita® Hammers HR2611F, XRH01, HR2631F	195173-3 
	 Makita® Hammers HR4001C, HR4002, HR4010C, HR4510C	196074-8 (Also includes chipping attachment)
	 Makita® Hammer HR4013C Makita® Hammer HR5212C	196537-4 (Not shown) 196858-4 (Not shown)

## Demolition

3/4" x 10' Hose 192108-A 	 Makita® Hammers HR4002, HR4010C, HR4510C	196074-8 (Also includes drilling attachment)
	 HR4013C HR5212C	196537-4 (Not shown) 196858-4 (Not shown)
Direct Connection No Connector Necessary	 Makita® Hammers HM0870C, HM1111C, HM1203C, HM1214C, HR4002, HR5212C	196571-4 
	 Makita® Hammers HM1307CB, HM1500B, HM1317CB, HM1810, HM1812	<b>NEW</b> 197172-1 

## Surfacing / Planing

Direct Connection No Connector Necessary	 Makita® 4-1/2" - 5" Grinders Except 9005B, Recommended GA5042C & 956 series grinders except 9564P	5" Grinding Shroud 195236-5  Replacement Brush Set 196880-1
	 Makita® 7" & 9" Grinders Except GA7911, GA7001L, Recommended GA7011C, GA7040S, GA9040S	7" Grinding Shroud 195386-6  Replacement Brush Set Y-00321
	 Planers PC5001C, PC5000C	No Attachment Necessary

## Tuck Pointing

Direct Connection No Connector Necessary	 Makita® 4-1/2" - 5" Grinders Except 9005B	<b>NEW</b> 196846-1 5" Tuck Point Guard
	 Makita® 4-1/2" - 5" SJSII® Grinders Only	<b>NEW</b> 196845-3 5" Tuck Point Guard

## XCV05Z

### 18V X2 LXT® Lithium-Ion (36V) Brushless Cordless 1/2 Gallon HEPA Filter Backpack Dry Vacuum, Tool Only

RUN TIME : Up to 90  
minutes of continuous  
operation using two 18V  
LXT® 5.0Ah batteries  
(batteries not included)

POWER : Powerful motor  
generates 53 CFM of  
suction power and 28.5"  
of water lift



## XCV04Z

### 18V X2 LXT® Lithium-Ion (36V) Cordless/Corded 2.1 Gallon HEPA Filter Dry Vacuum, Tool Only

POWER : Delivers 127  
CFM and 96" water lift

RUN TIME : Up to 65  
minutes of continuous  
run time using two 18V  
LXT® 5.0Ah batteries  
(batteries not included)





# ARE YOU READY?

Dust Extraction > **XTRACT VAC®**

## Xtract Vac® Accessories

Description	Part #	Description	Part #
Main Flat Nano Filters (pair)	P-79843	Crevice Nozzle	W6084
Main Flat HEPA Filters (pair) Tested filter efficiency certificate included	P-79859	Cuff Adapter for Hose P-79865 1-1/2" I.D. / 1-3/4" O.D.	P-70421
Fleece Nano Filters Bag (5/pk) <b>*RECOMMENDED TO PROLONG LIFE AND EFFICIENCY OF HEPA FILTER</b>	P-78293	Cuff Adapter for Hose P-70487 1" I.D. 1-3/8" / 1-1/2" O.D.	P-70415
Disposal Bag (5/pk)	P-70297	Quick Connect Adapter	P-70378
Anti-Static Hose 1-3/8" x 16' 1-1/2" I.D. / 1-3/4" O.D.	P-79865	Quick Connect Cuff	P-70384
Anti-Static Hose 1" x 11' - 6" I.D. 1-1/8" / O.D. 1-3/8"	P-70487	Flooring Set (8 pc.)	P-70312
3/4" x 10' Vacuum Hose I.D. 3/4" / O.D. 1" I.D. 1-1/2" / O.D. 1-3/4"	192108-A		

## SETTING A NEW STANDARD FOR JOBSITE VACUUMS WITH DUST EXTRACTION™

MEETS EPA (RRP) RULE HEPA VACUUMS WITH OPTIONAL HEPA MAIN FILTER INSTALLED



VC4710

### 12 GALLON WET/DRY VACUUM

Powerful 12 AMP Motor Generates 135 CFM and 92" of Water Lift

- Quiet operating sound level of 59 dB(A)
- Weights only 27 lbs
- Automatic Filter Cleaning System with blow-back feature for longer filter life
- Onboard tool-activated outlet starts and stops vacuum with power tool usage
- Variable speed control dial for a variety of applications
- Meets the EPA (RRP) rule for HEPA vacuums only with the optional main HEPA filter installed

Model VC4710 Includes: Main Flat Filters, 2/pk (P-79843), 1-3/8" x 16' Anti-Static Hose (P-79865), Crevice Nozzle (W6084), Replacement Cuff (P-70421), Fleece Nano Filter Bag (P-78293), Disposable Bag (P-70297)

Air Flow Rate	135 CFM
AMPS	12
Power Consumption	840.0 watts
Static Water Lift	92"
Working Sound Level	59 dB(A)
Equipped Filter Efficiency	99.95% of 2 microns
Peak Horsepower	4 HP
Gross Container Size	12 gal.
Dry Capacity	9 gal.
Wet Capacity	8 gal.
Dry Weight	27 lbs.
Shipping Weight	40.8 lbs.



## OSHA SILICA STANDARDS

Concrete Drilling

Concrete Surfacing or Crack Chasing/Tuck Pointing

OR

Use grinder equipped with commercially available **shroud and dust collection system**.

Dust collector must provide **25 CFM or greater of airflow per inch of wheel diameter** and have a **filter with 99% or greater efficiency** and a **filter-cleaning mechanism**.

**\*(vii) Handheld and stand-mounted drills (including chipping tools and rotary hammer drills)**

Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with **99% or greater efficiency** and a **filter-cleaning mechanism**.

**Use a HEPA-filtered vacuum** when cleaning holes.

\*WEBSITE: <https://www.federalregister.gov/articles/2016/03/25/2016-04800/occupational-exposure-to-respirable-crystalline-silica>,  
ARTICLE: Occupational Exposure to Respirable Crystalline Silica or OSHA rule 1926.1153 for Respirable crystalline silica.  
SEE [WWW.OSHA.GOV/SILICA](http://WWW.OSHA.GOV/SILICA) for more information

**JUNE 23, 2017**